

Biofiltration

Elecro Heaters



Elecro Heaters are a range of reliable heaters that are manufactured from top quality components and materials, offering the user precise digital temperature control to +/- 0.5°C. Safety features include a highly reliable flow switch and over-temperature protection by way of an integrated thermal cut out.

- Titanium flow tubes for Salt or Freshwater applications.
- Digital temperature display and control to 0.5°C [0-40°C].
- External reversible flow switch allows safe operation as low as 1m³/hour.
- Integral Schneider contactor.
- High limiting safety thermostat.
- Anti-cycle protection.
- Swivel feet can be rotated to permit either wall or floor mounting.
- 4 Bar pressure rating.
- 1½" or 50mm solvent weld inlet and outlets.



Electro Heaters

Code	Product	Power (kW)	Current (A)	Minimum Flow Rate (m ³ /hr)	Maximum Flow Rate (m ³ /hr)	Inlet/Outlet Size	Dimension Length (mm)	Approx. Shipping Weight (kg)
Single phase 230V								
8034	2kW Titanium Electric Heater	2	9	1	17	1/2" or 50mm	462	4
8009	3kW Titanium Electric Heater	3	13	1	17	1 1/2" or 50mm	462	4
8035	4kW Titanium Electric Heater	4	18	1	17	1 1/2" or 50mm	462	4
8010	6kW Titanium Electric Heater	6	27	1	17	1 1/2" or 50mm	462	5
8011	8kW Titanium Electric Heater	8	35	1	17	1 1/2" or 50mm	592	5
Three phase 400V								
8012	6kW Titanium Electric Heater	6	9	1	17	1 1/2" or 50mm	592	6
8013	8kW Titanium Electric Heater	8	13	1	17	1 1/2" or 50mm	592	6
8037	12kW Titanium Electric Heater	12	18	4	17	1 1/2" or 50mm	592	8
8038	15kW Titanium Electric Heater	15	22	4	17	1 1/2" or 50mm	592	9
8039	18kW Titanium Electric Heater	18	26	4	17	1 1/2" or 50mm	592	10

