

# Biofiltration

## Argonaut AG Series Pumps

The Argonaut AG Series of pumps are a cost effective, reliable range of pumps, suitable for use in both freshwater and saltwater applications. The European manufactured motors are suitable for lower flow applications with enough head to still drive most mechanical filters.

- Heavy duty long life IP55 rated motor.
- Quiet running 55dB rating.
- Glass filled polypropylene tank has a high chemical resistance.
- High grade stainless steel motor shaft.
- AISI 316 carbon/ceramic mechanical seal.
- 1.65 Litre strainer basket and clear body lid for easy inspection.
- Quick connect barrel unions for UPVC pipe [supplied with both 1.1/2" or 50 mm].
- Drain plug.
- Self-priming up to 1.8 metres.
- Suitable for Freshwater and Saltwater applications.

### Available separately

Full range of pipe and fittings  
Pump suction strainer



## Argonaut AG Series Pumps

Code	Product	Power Max (kW)	Current (A)	Max working head (m)	Flow Rate Qmax (m <sup>3</sup> /h)	Inlet/Outlet	Total length (mm)	Approx. Shipping Weight (kg)
Argonaut AG - 1 phase 240V/50Hz								
7290	Argonaut AG8 Pump	0.29	1.45	8	9	1½" or 50	476	8
7291	Argonaut AG10 Pump	0.36	1.70	9	11	1½" or 50	476	8
7292	Argonaut AG14 Pump	0.49	2.80	11	14	1½" or 50	476	8
7293	Argonaut AG16 Pump	0.67	3.00	13	16	1½" or 50	476	8

Performance Curves for Argonaut AG Pumps

